WAFER LED I SURFACE MOUNT


57710 / 57712 / 57714

- Die Cast Aluminum
- Size options between 5", 7" and 10"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Availbale in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3.25" and 4" Outlet Box (Pancake NOT recommended)
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

MODEL	DIMENSION
57710	5"D x 0.5"H
57712	7"D x 0.5"H
57714	10"D x 0.5"H

HANGING WEIGHT	
0.88 LB	
1.21 LB	
1.75 LB	

LAMPING

			LUMENS	COL		
MODEL	BULB TYPE	CRI	INIT DEL	TEMP.	DIMMABLE	INPUT
57710	(1) 10W PCB LED (Integrated)	90+	700 600	3000K	ELV	120V
57712	(1) 15W PCB LED (Integrated)	90+	1050 900	3000K	ELV	120V
57714	(1) 20W PCB LED (Integrated)	90+	1400 1200	3000K	ELV	120V

Job Name	:
Job Type	:
Quantity	:
Comments	•





ADDITIONAL: RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com



MATERIAL: Die Cast Aluminum PMMA Acrylic Diffuser

AVAILABLE SIZES: 5" | 7" | 10"

RATINGS:

White (WT)

Bronze (BZ)

Satin Nickel (SN)

ETL/cETL IP65 Wet Location Energy Star CA Title 24 ADA

